



QAQC LAB

www.qclabequipment.com

Octagon 200



The sieve shaker Octagon 200 is suitable for all sieving tasks in laboratories as well as onsite and provides optimum sieving action for fast and reproducible results.

It is robust, compact and sufficiently lightweight to be portable. Its electromagnetic drive combined with a 3D sieving motion ensures excellent separation efficiency in a short amount of time.

A digital display as well as a quick-release clamping system make operation very easy and straightforward.

Advantages

- Easy-to-use sieve clamping system
- Accepts up to 8 full height 200 mm or 8" diameter sieves
- Dry and wet sieving
- 10 amplitude settings & digital timer
- 3D sieving motion allows for high separation efficiency and non blinding sieving action
- Different voltages available
- No mechanical moving parts
- Compact & portable
- Complies with the requirements of AASHTO T 27

QUICK QUOTE

ONLINE PRICING



A wet sieving kit includes a top clamping plate with a Perspex cover, and spray rose, watertight O-ring seals and a stainless steel receiver with drainage spout. O-ring seals may also be ordered separately.



Vertical vibration is generated by the on/off frequency of the electromagnetic drive. However, vertical vibration is not enough to impart the correct movement for sieving. The shaker also needs to twist the sieve stack - this rotating action ensures the sample passes over the full surface of the sieve and the maximum number of apertures to give rapid accurate results

Specifications	Octagon 200
Range	20 µm to 125 mm
Drive / sieving motion	electromagnetic 3D
Max. batch / feed capacity	3 kg
Max. number of sieves	8 full height / 16 half height (200 mm or 8" sieves)
Amplitude	0 - 3 mm, digital setting in 10 steps
Time display	digital, 0:10-99:50 min:sec
Interval operation	yes (one mode)
Suitable for dry sieving	yes
Suitable for wet sieving	yes
Serial interface	-
Sieve diameter	100 / 200 mm, 3" / 8"
Max. height of sieve stack	450 mm
Clamping device	quick-release clamping system (included)
Model	benchtop
Protection code	IP 54
Electrical supply	different voltages available
Power connection	1 - phase
W x H x D	418 x 232 x 435 mm
Net weight	~ 35 kg